

Bearing Checker



BearingChecker is a portable instrument for fast and easy measurement of bearing condition in preventive maintenance. The instrument is push button controlled and basic measurement data are entered manually.

BearingChecker measures shock pulses, either with a built-in probe (BC200) or with an external transducer. The instrument can also be used as an electronic stethoscope for detecting machine sound irregularities.

Measuring results are indicated by green-yellow-red symbols along with detailed evaluation of measurement values. Measurement results can also be transferred to a file for further processing, e.g. in Microsoft Excel.

For prepared kits containing instruments, carrying case, charger, charger cable, etc., see TD-573.

Technical specifications

Material, casing:	copolyester/TPE
Size:	BC200: 207x74x41 mm (8.1x2.9x1.6 in) BC250: 184x74x41 mm (7.2x2.9x1.6 in)
Weight:	BC200: 335 g (11.8 ounces) BC250: 300 g (10.6 ounces)
Protection class:	IP65
Keypad:	sealed, snap action
Display:	2.4" Color TFT LCD Display
Power supply:	3.63 V Lithium Ion, USB rechargeable
Battery life:	> 25 hours of normal use
Operating temperature:	-10° to +50 °C (14° to 122 °F)
General functions:	battery status display, transducer line test, metric or Imperial units of measurement, menus with symbols, storage of up to 10 measurement values
Input connector:	mini coax, for external shock pulse transducers

Output connector: mini-B USB (adapter allows 3.5 mm stereo jack for headphones)

Shock pulse measurement

Measurement technique: dBm/dBc, measuring range -9 to 90 dBsv, ± 3 dBsv

Transducer type: built-in probe, external 40000 or 42000 transducer, TRA73, TRA74, or TRA75

Condition indication: green, yellow, and red symbols

Stethoscope

Earphone mode: 7 level amplification

Transducer type: built-in probe or external 40000 transducer

Part numbers

BC200 BearingChecker with probe, excl. options
BC250 BearingChecker without probe, excl. options

Options

CAB52	Measuring cable, 1.5 m, mini coax - BNC slip-on
CAB94	Charger cable, USB type A to mini-B USB, 1.5 m
CAS24	Carrying case, plastic with foam inlay set for 1 BC/VC instrument, 326x222x116 mm
CAS29	Carrying case, plastic with foam inlay set for 2 BC/VC instruments, 437x379x130 mm
EAR12	Headphones with eardefenders (TD-404)
TRA73	External transducer with probe (TD-250)
TRA74	Transducer with quick connector (TD-251)
TRA75	Transducer with quick connector, angled (TD-252)
18103	Cable adapter, mini-B USB to 3.5 mm stereo jack
18226	Kit for screen protection (2 pcs screen protector)
90647	Charger, 100-240 V, 50-60 Hz, 6 W
93363	Cable adapter, mini coax - BNC
93062	Cable adapter, BNC - TNC, plug-jack

Spare parts

18128 Rubber sleeve, built-in probe



SPM Instrument AB • Box 504 • SE-645 25 Strängnäs • Sweden
Tel +46 152 22500 • info@spminstrument.se • www.spminstrument.com



Technical data are subject to change without notice.
ISO 9001 certified. © Copyright SPM 2021-01. TD-554 B Rev.4